Red Lion HMI - Email Server Update

- 1. Insert Compact Flash Card
 - a. Open the Off-Board Electrical Cabinet
 - b. Insert flash card into slot on the hinge side of the back of the Red Lion.



- 2. Remove Power Connector from Red Lion for 10sec and reinsert.
 - a. On power up the screen should display "FLASHING FROM CF"
 - b. Next the screen will display "LOADING FROM CF"
- 3. At this point you will need to log into the display with your user name and password. The default username is "user" and the default password is "user". If you are updating a Red Lion and have changed the user password, you should be able to log in with those credentials.
- 4. Press the 6th soft button from the top of the display.



5. The following menu screen should load. Go to Email Setup.



- 6. On this you can setup SMTP email server. The server must use simple username and password authentication. (Note: The Red Lion does not support TLS/SSL)
 - a. At this point you can load our default email settings or load your own.
 - b. Press the button marked "Load Default Setup"



c. The following settings should be loaded.



d. You can "tap" on any field to change the data. Tap once to high selection, and then tap again to bring up the key pad. The following screens show how to get around the Key Pad.

				Low	ver C	Case					
•	14Jan-2013			E	Mail \$	Settin	igs				19.53.27
•											_
				EM	AIL_C	ONTA			-	Γ	
_			2.4		SYMBOL		PREU	HEXT	ENTER	EXIT	
•		w	e	r	Ľ	y 		<u> </u>	°	P	
	LOCK	a	5	d	f	9	h	ť	k	1	
	SHIFT	z	×	C	Y	ь	n	m	SP	ACE	
٠		Men	•					Previou Page	IS		
•				0							
м											







7. Go To E-Mail Contact Page.



- 8. Entering email contacts.
 - a. You can use any email address for your contact.
 - b. You can use a cell phone number with your carriers SMS email address. You will get this type of email on phone faster than email. You can find your carriers email address using Google, search for "email to text". Here are a few of the more common ones:

AT&T: number@txt.att.net or number@mms.att.net
Qwest: number@qwestmp.com
T-Mobile: number@tmomail.net
Verizon: number@vtext.com
Sprint: number@messaging.sprintpcs.com or number@pm.sprint.com
Virgin Mobile: number@vmobl.com
Nextel: number@messaging.nextel.com
Alltel: number@message.alltel.com
Metro PCS: number@mymetropcs.com
Powertel: number@ptel.com
Boost Mobile: number@myboostmobile.com
Suncom: number@tms.suncom.com
Tracfone: number@mmst5.tracfone.com
U.S. Cellular: number@email.uscc.net



9. The system can be tested by pressing the "Send Test E-Mail" button on the previous page.

• 14-Jan-2013	E-Mail Settings	13:32:39
Lida Suff Dons Unit 3 Reve Loge Loge	SMTP SETTINGS erver IP Address 24121228.50 cover Port 25 3db Number 176 ne 15 techReasiscerusshsystems.con techReasiscerusshtrasiscerusshsystems.con techReasiscerusshsystems.con techReasi	ī
 Mean 	Send Text E-Mail Befault Setup	Hext Page
		Press Here